



TECHNICAL RUBBER COMPANY
 dba TECH INTERNATIONAL
 200 EAST COSHOCTON STREET
 P.O. BOX 486
 JOHNSTOWN, OHIO 43031
 (740) 967-9015 (ph.)
 (740) 967-1039 (fax.)

Page 1 of 7

EFFECTIVE: 4/10/03
 SUPERCEDES: 1/23/02

MSDS NO.: 735
 REVISION NO.: 6

TECH BEAD SEALER

MATERIAL SAFETY DATA SHEET



SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: TECH BEAD SEALER
CATALOG NUMBER(S): 735, 735G, 735-5G, 735-55G
PRODUCT USE: TIRE MOUNTING SEALANT

FOR CUSTOMER SERVICE INFORMATION, CONTACT:
 (740) 967-9015 or (800) 433-8324

EMERGENCY TELEPHONE NUMBER (24 hrs.): CHEMTREC (800) 424-9300
 CHEMTREC International (703) 527-3887

SECTION 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT (COMMON NAME)	CAS NO.	% (by vol.)	OSHA PEL	ACGIH TLV	NIOSH PEL
Light Aliphatic Naphtha	64742-89-8	>89	100 ppm TWA; 400 mg/m3 TWA	400ppm	100 ppm TWA; 400 mg/m3 TWA; 1000 ppm IDLH

EXPOSURE LIMITS ARE TIME WEIGHTED AVERAGES (TWA). SHORT-TERM EXPOSURE LIMITS (STEL) AND CEILING (C) ARE INCLUDED IF ESTABLISHED.

NOTES	
1	A complex stream of predominantly C6 to C9 hydrocarbons, exact composition varies. Occupational exposure limits based on limits for petroleum distillates/naphtha/rubber solvent.
*	Not Established

SECTION 3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance & Odor: Black liquid with a high viscosity. Strong solvent odor.
Health Hazards: May cause eye and skin irritation. Exposure to vapor mist is possible.
Physical Hazards: Flammable liquid. Do not use near open flame. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, etc.
R-Phrases: R11 Highly Flammable; R36/38 Irritating to eyes and skin
S-Phrases: S16 Keep away from sources of ignition - no smoking; S25 Avoid contact with eyes; S33 Take precautionary measures against static discharge; S51 Use only in well-ventilated areas
Hazard Symbol: F Highly Flammable

TECH BEAD SEALER
 TECHNICAL RUBBER COMPANY
 Page 2 of 7

MATERIAL SAFETY DATA SHEET

EYE CONTACT	Exposure to product may cause eye irritation. Symptoms include stinging, tearing, redness and swelling.
INHALATION	Exposure to vapor or mist is possible. The short-term inhalation toxicity is low. Breathing small amounts of vapors during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful. Symptoms typically seen at air concentrations above the recommended exposure limits may include: irritation to nose, throat and respiratory system, metallic taste, muscle weakness. Initial central nervous system (CNS) excitation (euphoria, exhilaration, light-headedness) followed by CNS depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other CNS effects (confusion, impaired coordination, coma and possibly death).
INGESTION	Single dose oral toxicity is low. Symptoms may include: gastrointestinal irritation (nausea, vomiting, diarrhea), CNS depression.
SKIN CONTACT	Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry skin. Symptoms include: redness, burning, drying, cracking and skin burns.
TARGET ORGANS EFFECTED	CNS, liver, kidneys, skin, eyes

CARCINOGENICITY - LISTED BY:

ACGIH	No	IARC	No	NTP	No	OSHA	No
--------------	----	-------------	----	------------	----	-------------	----

SECTION 4. FIRST AID MEASURES

EYE CONTACT	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes with water for at least 20 minutes while holding eyelids apart. If symptoms persist, seek medical attention.
INHALATION	If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen. Keep person warm and quiet.
INGESTION	If swallowed, DO NOT induce vomiting. This material is an aspiration hazard. If person is drowsy or unconscious, place on left side with head down. Seek immediate medical attention.
SKIN CONTACT	Remove contaminated clothing. Wash exposed area with soap and water. Launder contaminated clothing before reuse. If symptoms persist, seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD	20.0 ° F (-6.7 ° C)
LEL	1.0%
UEL	8.0 %
EXTINGUISHING MEDIA	Foam, carbon dioxide or dry chemical
SPECIAL FIREFIGHTING PROCEDURES	Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires.

TECH BEAD SEALER
TECHNICAL RUBBER COMPANY
Page 3 of 7

MATERIAL SAFETY DATA SHEET

FLASH POINT AND METHOD	20.0 °F (-6.7 °C)
UNUSUAL FIRE AND EXPLOSION HAZARDS	Never use a welding or cutting torch on or near container (even when empty) because product (even just residue), can ignite explosively. All 5-gallon or larger metal containers should be grounded and bonded when material is being transferred. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources distant from the material handling point.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL	Eliminate all sources of ignition (flames, pilot lights, electrical sparks) and absorb material on vermiculite, floor absorbent or other absorbent material.
LARGE SPILL	Eliminate all sources of ignition (flames, pilot lights, electrical sparks, etc.). Persons not wearing appropriate protective equipment should be excluded from area of spill until cleanup has been completed. Stop spill at source. Prevent material from entering drains, sewers, streams, or other bodies of water. Prevent from spreading by using dikes, booms, etc. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled material into clean, approved containers for recovery or disposal. Absorb unrecoverable material onto vermiculite, floor absorbent or other absorbent material, and transfer into clean approved containers for disposal.

SECTION 7. HANDLING AND STORAGE

Containers of this product may be hazardous when emptied. Since emptied containers retain product residues (vapors, liquid, and/or solids), all hazard precautions given in this data sheet must be observed.

Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering, pouring or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form which may ignite the vapors of the flammable liquids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION	Chemical splash goggles in compliance with OSHA regulations are advised, however OSHA regulations also permit other types of safety glasses. Consult your safety equipment representative.
RESPIRATORY PROTECTION	If workplace exposure limit (s) of product or any component is exceeded (See Section 2), a NIOSH/MSHA approved respirator is advised in the absence of proper environmental control. OSHA regulations permit other NIOSH/MSHA approved respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.
SKIN PROTECTION	Wear resistant gloves, such as: polyvinyl alcohol, nitrile.
ENGINEERING CONTROLS	Provide sufficient mechanical (general or local exhaust) ventilation to maintain exposure below OEL(s). Explosion-proof ventilation system is acceptable.
OTHER PROTECTIVE EQUIPMENT	To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
OTHER HYGIENIC AND WORK PRACTICES	Use good personal hygiene work practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash before reuse.

MATERIAL SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INITIAL BOILING POINT	209 - 230 ° F (98.3 - 110 ° C) @ 760.00 mm Hg
VAPOR PRESSURE	110.50 mm Hg @ 100.00 ° F
VAPOR DENSITY (air = 1)	3.30
SPECIFIC GRAVITY (water = 1)	0.75 @ 60.00 ° F
% VOLATILES	89.1%
VOC CONTENT	5.52 lbs./gal (660.9 g/L)
EVAPORATION RATE	3.6 (n-Butyl Acetate = 1)
pH	Not Applicable
APPEARANCE	Black liquid, high viscosity
ODOR	Strong solvent

SECTION 10. STABILITY AND REACTIVITY

STABILITY	Stable
HAZARDOUS POLYMERIZATION	Cannot occur
INCOMPATIBILITY (materials or conditions to avoid)	Strong oxidizers, strong acids
HAZARDOUS DECOMPOSITION PRODUCTS	Carbon dioxide, carbon monoxide, various hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

No data is specifically available for this product and therefore this toxicological information is based on testing completed with ingredients.

TOXICOLOGICAL DATA **LIGHT ALIPHATIC NAPHTHA:** LD50 Oral Rat >25000mg/kg
LC50 Inhalation Rat 14000-16000 ppm for 4 hours
LD50 Dermal Rabbit >5000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. Biodegradable, rapid volatilization.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal of material should be done in accordance with all Federal (40 CFR Part 261), State and Local environmental control regulations. In its unused state, the product exhibits the EPA hazardous waste characteristic for ignitability (RCRA waste code D001).

MATERIAL SAFETY DATA SHEET

SECTION 14. TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME (49 CFR 172.101)	Adhesives
HAZARD CLASS (DOT, IATA)	3
HAZARD CLASS (IMO)	3
ID NUMBER	UN 1133
PACKING GROUP	II
ADDITIONAL DESCRIPTION	Petroleum Naptha
LABELS REQUIRED	Flammable Liquid (49 CFR 172.419)
2000 EMERGENCY RESPONSE GUIDEBOOK NO.	128
EmS NUMBER	3-05
REPORTABLE QUANTITY (DOT)	As D001 hazardous waste - 100 lbs. (45.4 kg.)

SECTION 15. REGULATORY INFORMATION

This product contains the following toxic substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (Emergency Planning and Community Right-To-Know Act) of 1986 and of 40 CFR Part 372:

CHEMICAL	CAS NO.	% COMPOSITION (by vol.)
Light Aliphatic Naphtha	64742-89-8	>89%

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 Chemical Substance Inventory List (40 CFR Part 710).

STATE REGULATIONS

The following chemicals are listed by individual states; other specific health and safety data in other sections of this MSDS may also be applicable for state requirements. For more details on state regulatory requirements contact the appropriate state.

California, Florida, New Jersey, Pennsylvania, Minnesota, and Massachusetts have the following chemical(s) on their Right-To-Know Chemical list:

n-Heptane (142-82-5)• 16%

- Component(s) of Light Aliphatic Naphtha

INTERNATIONAL REGULATIONS

INVENTORY STATUS (components):

LIGHT ALIPHATIC NAPHTHA: Listed on the following international inventories: AICS (Australia), DSL (Canada), ECL (South

MATERIAL SAFETY DATA SHEET